

SIMATIC S7-300, CPU 313C COMPACT CPU WITH MPI, 24 DI/16 DO, 4AI, 2AO 1 PT100, 3 FAST COUNTERS (30 KHZ), INTEGRATED 24V DC POWER SUPPLY, 32 KBYTE WORKING MEMORY, FRONT CONNECTOR (2 X 40PIN) AND MICRO MEMORY CARD REQUIRED

General information	
HW functional status	01
Firmware version	V2.0.0
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.2 SP1 or higher
Supply voltage	
Rated value (DC)	Yes
<ul style="list-style-type: none"> 24 V DC 	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> permissible range, lower limit (DC) 	20.4 V
<ul style="list-style-type: none"> permissible range, upper limit (DC) 	28.8 V
Input current	
Current consumption (rated value)	700 mA
Current consumption (in no-load operation), typ.	150 mA
Inrush current, typ.	11 A
Power loss	
Power loss, typ.	14 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated 	32 kbyte; For program and data
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> Plug-in (MMC) 	Yes
<ul style="list-style-type: none"> Plug-in (MMC), max. 	8 Mbyte
<ul style="list-style-type: none"> Data management on MMC (after last programming), min. 	10 y
Backup	
<ul style="list-style-type: none"> present 	Yes; Guaranteed by MMC (maintenance-free)
<ul style="list-style-type: none"> without battery 	Yes; Program and data

CPU processing times	
for bit operations, typ.	0.1 μ s
for bit operations, max.	0.2 μ s
for word operations, typ.	0.2 μ s
for fixed point arithmetic, typ.	2 μ s
for floating point arithmetic, typ.	3 μ s

CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs OBs, SDBs); the maximum number of loadable blocks can be reduced by the MMC being used.
DB	
• Number, max.	511; Number range: 1 to 511
• Size, max.	16 kbyte
FB	
• Number, max.	512; Number range: 0 to 2047
• Size, max.	16 kbyte
FC	
• Number, max.	512; Number range: 0 to 2047
• Size, max.	16 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	16 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	1; OB 20
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	1; OB 80
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	8
• additional within an error OB	4

Counters, timers and their retentivity	
S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	256
Counting range	
— lower limit	0

— upper limit	999
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	256
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	all
Flag	
• Number, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Number, max.	511; from DB1 to DB511
• Size, max.	16 kbyte
• Retentivity adjustable	No
• Retentivity preset	Yes
Local data	
• per priority class, max.	510 byte
Address area	
I/O address area	
• Inputs	1 kbyte
• Outputs	1 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Default addresses of the integrated channels	
— Digital inputs	124.0 to 126.7
— Digital outputs	124.0 to 125.7
— Analog inputs	752 to 761
— Analog outputs	752 to 755

Digital channels	
• Inputs	992
— of which central	992
• Outputs	992
— of which central	992
Analog channels	
• Inputs	248
— of which central	248
• Outputs	124
— of which central	248
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	none
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	6
Rack	
• Racks, max.	4
• Modules per rack, max.	8; In rack 3 max. 7
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Backup time	6 wk; At 40 °C ambient temperature
• Deviation per day, max.	10 s
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• Granularity	1 hour
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
Digital inputs	

Number of digital inputs	24
integrated channels (DI)	24
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+15 to +30V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms
for counter/technological functions	
— at "0" to "1", max.	16 µs
Cable length	
• shielded, max.	1 000 m; 100 m for technological functions
• unshielded, max.	600 m
Digital outputs	
Number of digital outputs	16
integrated channels (DO)	16
Short-circuit protection	Yes; Clocked electronically
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" permissible range, max.	500 mA
• for signal "1" permissible range for 0 to 60 °C, max.	500 mA
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	8 A
— up to 60 °C, max.	4 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Analog inputs	
Number of analog inputs	

<ul style="list-style-type: none"> • For voltage/current measurement 	4
<ul style="list-style-type: none"> • For resistance/resistance thermometer measurement 	1
integrated channels (AI)	4+1
permissible input voltage for current input (destruction limit), max.	5 V; Permanent
permissible input current for voltage input (destruction limit), max.	0.5 mA; Permanent
Technical unit for temperature measurement adjustable	Yes; Degrees Celsius / degrees Fahrenheit / Kelvin
Input ranges	
<ul style="list-style-type: none"> • Current 	Yes
<ul style="list-style-type: none"> • Resistance thermometer 	Yes
<ul style="list-style-type: none"> • Resistance 	Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • 0 to +10 V 	Yes
<ul style="list-style-type: none"> • Input resistance (0 to 10 V) 	100 k Ω
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA 	Yes
<ul style="list-style-type: none"> • Input resistance (0 to 20 mA) 	100 Ω
<ul style="list-style-type: none"> • -20 mA to +20 mA 	Yes
<ul style="list-style-type: none"> • Input resistance (-20 mA to +20 mA) 	100 Ω
<ul style="list-style-type: none"> • 4 mA to 20 mA 	Yes
<ul style="list-style-type: none"> • Input resistance (4 mA to 20 mA) 	100 Ω
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> • Pt 100 	Yes
<ul style="list-style-type: none"> • Input resistance (Pt 100) 	10 M Ω
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> • 0 to 600 ohms 	Yes
<ul style="list-style-type: none"> • Input resistance (0 to 600 ohms) 	10 M Ω
Analog outputs	
Number of analog outputs	2
integrated channels (AO)	2
Output ranges, voltage	
<ul style="list-style-type: none"> • 0 to 10 V 	Yes
<ul style="list-style-type: none"> • -10 V to +10 V 	Yes
Output ranges, current	
<ul style="list-style-type: none"> • 0 to 20 mA 	Yes
<ul style="list-style-type: none"> • -20 mA to +20 mA 	Yes
<ul style="list-style-type: none"> • 4 mA to 20 mA 	Yes
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	

• Resolution with overrange (bit including sign), max.	12 bit
• Integration time, parameterizable	Yes; 2,5 / 16,6 / 20 ms

Analog value generation for the outputs

Integration and conversion time/resolution per channel

• Resolution with overrange (bit including sign), max.	12 bit
• Conversion time (per channel)	1 ms

Encoder

Connectable encoders

• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA

Errors/accuracies

Basic error limit (operational limit at 25 °C)

• Voltage, relative to input range, (+/-)	0.7 %
• Current, relative to input range, (+/-)	0.7 %
• Resistance, relative to input range, (+/-)	3 %
• Resistance thermometer, relative to input range, (+/-)	3 %
• Voltage, relative to output range, (+/-)	0.7 %
• Current, relative to output range, (+/-)	0.7 %

Interfaces

MPI

• Cable length, max.	50 m; without repeater
----------------------	------------------------

1. Interface

Interface type	Integrated RS 485 interface
----------------	-----------------------------

Physics	RS 485
---------	--------

Isolated	No
----------	----

Power supply to interface (15 to 30 V DC), max.	200 mA
---	--------

Functionality

• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No

MPI

• Number of connections	8
• Transmission rate, max.	187.5 kbit/s

Services

— PG/OP communication	Yes
— Routing	No

— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes

Communication functions

PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD loops, max.	4
• Number of GD packets, max.	4
• Number of GD packets, transmitter, max.	4
• Number of GD packets, receiver, max.	4
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 byte
• User data per job (of which consistent), max.	64 byte
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	8
• usable for PG communication	7
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	7
• usable for OP communication	7
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	7
• usable for S7 basic communication	4
— reserved for S7 basic communication	4

- adjustable for S7 basic communication, min. 0
- adjustable for S7 basic communication, max. 4
- usable for routing No

S7 message functions

Number of login stations for message functions, max.	8; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	20

Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	2

Status/control

- Status/control variable Yes
- Variables Inputs, outputs, memory bits, DB, times, counters
- Number of variables, max. 30
 - of which status variables, max. 30
 - of which control variables, max. 14

Forcing

- Forcing Yes
- Forcing, variables Inputs, outputs
- Number of variables, max. 10

Integrated Functions

Number of counters	3; 3 channels (see "Technological Functions" manual)
Counting frequency (counter) max.	30 kHz
Frequency measurement	Yes
Number of frequency meters	3; 3 channels up to max. 30 kHz (see "Technological Functions" manual)
controlled positioning	No
integrated function blocks (closed-loop control)	Yes; PID controller (see "Technological Functions" manual)
PID controller	Yes
Number of pulse outputs	3; 3 channels pulse width modulation up to max. 2.5 kHz (see "Technological Functions" manual)
Limit frequency (pulse)	2.5 kHz

Potential separation

Potential separation digital inputs

- Potential separation digital inputs Yes
- between the channels, in groups of 16; and 8
- between the channels and backplane bus Yes

Potential separation digital outputs

• Potential separation digital outputs	Yes
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
Potential separation analog inputs	
• Potential separation analog inputs	Yes; common for analog I/O
• between the channels and backplane bus	Yes
Potential separation analog outputs	
• Potential separation analog outputs	Yes; common for analog I/O
• between the channels and backplane bus	Yes

Configuration

Configuration software

- | | |
|----------|---------------|
| • STEP 7 | Yes; V5.1 SP2 |
|----------|---------------|

Programming

- | | |
|--------------------------------|----------------------|
| • Command set | see instruction list |
| • Nesting levels | 8 |
| • System functions (SFC) | see instruction list |
| • System function blocks (SFB) | see instruction list |

Programming language

- | | |
|------------|-----|
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |
| — SCL | Yes |
| — GRAPH | Yes |
| — HiGraph® | Yes |

Know-how protection

- | | |
|---|-----|
| • User program protection/password protection | Yes |
|---|-----|

Dimensions

Width	120 mm
Height	125 mm
Depth	130 mm

Weights

Weight, approx.	660 g
-----------------	-------

last modified:	10/26/2017
-----------------------	------------